

# **TC-508**

Professional
Two-way Radio
Affordable & Reliable









- Tough & Light-weight
- Robust & Reliable
- Longer Battery Life
- Enhanced Voice Quality



# TC-508

# **Professional Two-way Radio**

## Leading Features

## ■ Tough & Light-weight

TC-508 has a light-weight but exceptionally strong body, allowing it to be carried about easily and to survive harsh conditions.

### ■ Robust & Reliable

TC-508 is built to survive the hard knocks, drops and some tought environments of its users. It meets or exceeds the HYT 5-year ALT test.

## ■ Longer Battery Life

TC-508 is equipped with a 1650mAh battery that enables you to transmit and receive, on a 5-5-90 basis, for up to 14 hours.

### ■ Enhanced Voice Quality

TC-508 employs advanced voice technologies to better the sound quality during your communication.

## **Main Functions**

**High/Low Power Switch** 

Wide/Narrow Band Switch

**Monitor** 

CTCSS/CDCSS and Squelch Tail Elimination

**Channel Scan** 

**Battery Save** 

**Low Battery Alert** 

**Busy Channel Lockout** 

**Time-out Timer (TOT)** 

**PC Programmable** 

**Wired Clone** 

Squelch Levels Selectable







# **Recommended Applications**

- Hospitality
- Manufacturing
- Retail

- Education
- Construction
- Security

## **Accessories**

Standard Accessories Li-Ion Batter Belt Clip Rapid-Rate Charger (for Li-lon Battery
Strap

Power Adapter Antenna

## Optional Accessories



Li-lon Battery (1300mAl BL1301



Vehicle Power Adapt



ix-unit Switching Power



Remote Speaker



Earbud with on-MIC PTT & VOX ESM12



D-earset with in-Line MIC & VOX EHM15



D-earset with Boom MIC & VOX EHM16



Earpiece with on-MIC
PTT & Transparent
Acoustic Tube EAN12



Transparent Acoustic Tube (for use with remote speaker microphone) ESS08



Nylon Carrying Case (not swivel)(black) NCN001



Receive-Only Earpiece (for use with remote speake microphone) ESS07

Note: Pictures above are for reference only and may vary from actual product.

Frequency Range(MHz)	VHF: 146-174 UHF: 450-470
Channel Capacity	16
Channel Spacing(KHz)	25 /12.5
Operating Voltage(V)	7.4
Battery	1650mAh (Li-lon Battery)
Battery Life (5-5-90 Duty Cycle)	14 hours
Frequency Stability(ppm)	±2.5
Operating Temperature( $^{\circ}\!\mathbb{C}$ )	-20~+65
Antenna Impedance( $\Omega$ )	50
Dimensions (H $\times$ W $\times$ D)(with battery, without antenna)(mm)	113×54×35
Weight (with antenna & battery)(g)	280

Power Output	5W/2W(VHF) 4W/2W(UHF)
Modulation	16K0F3E/11K0F3E
Spurious and Harmonics	≤-26dBm (<1G)
FM Noise	40/35dB
Audio Distortion	<b>≤</b> 5 %
Modulation Limiting	≤5KHz (25KHz) ≤2.5KHz (12.5KHz)
Audio Response	

All Specifications are tested according to applicable standards, and subject to change without notice due to continuous development.

Sensitivity	≤0.251uV/0.282uV
Adjacent Channel Selectivity	65dB/55dB
Intermodulation	60dB
Spurious Response Rejection	65dB
S/N	45dB/40dB
Rated Audio Power Output	0.5W(Speaker impedance: 16 Ohm)
Rated Audio Distortion	
Conducted Spurious Emission	-57dBm < 1GHz -47dBm > 1GHz









## **Hytera Communications Corporation Limited**

Address: HYT Tower, Hi-Tech Industrial Park North, Beihuan Rd., Nanshan District, Shenzhen, China

Http://www.hytera.com Stock Code: 002583.SZ

Hytera retains right to change the product design and specification. Should any printing mistake occur,  $Hytera\ doesn't\ bear\ relevant\ responsibility.\ Little\ difference\ between\ real\ product\ and\ product\ indicated$ by printing materials will occur by printing reason.

## Your Local Dealer



Dumlupınar Mah. Yumurtacı Abdi Bey Cad. Gümüşdere Çıkmazı Sok. Concord İstanbul No: 1/E C Blok Kat: 22 0:209 Kadıköy - İstanbul Tel: +90 (216) 771 69 94 www.northera.com.tr

Northera Haberlesme Çözümleri A.S